

# TECHNICAL DATASHEET **ALUNI S3**

Ref. 9ALU160

Sizes 37 >> 47

MULTIPURPOSE

HIGH SHOE



#### **HIGH SHOES**





- Flexible and water repellent upper
- Scuff cap front and back
- Insole foam with pads: comfort

PURCHASE PACKAGING			
REF.	EU	US	
9ALU160037	37	4.5	6
9ALU160038	38	5.5	6
9ALU160039	39	6	6
9ALU160040	40	7	6
9ALU160041	41	8	6
9ALU160042	42	8.5	6
9ALU160043	43	9.5	6
9ALU160044	44	10	6
9ALU160045	45	11	6
9ALU160046	46	11.5	6
9ALU160047	47	12.5	6

## **DESCRIPTION**

ALUNI combines lightness and a sporty look. Equipped with an EVA / rubber nitrile outsole, this sneaker is remarkably flexible. The HI-POLY foam of the insole and its pads guarantee great wearing comfort. Its Oxford fabric upper is waterproof.

### **SECTORS**

**Service** 

**Second work** 

Handyman

**Light industry** 



#### **TECHNICAL FEATURES**

Closure Lacing Anti perforation sole Textile

Toe capCompositeWork environmentMultipurposeSub-familyHigh shoeColorBlack/yellow/grey

**Upper**Water repellent Oxford fabric Insole
with TPU
HI-POLY Foam with pads

Midsole EVA Wearing sole Nitrile rubber

**Lining** Mesh

#### INSTRUCTIONS FOR USE AND STORAGE

#### Instructions for use:

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

#### Storage instructions

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

#### Cleaning instructions:

- Regularly clean the shoes by using brushes, cleaning clothes.

#### **LEGISLATION**

CE

EN ISO 20345:2011



**S3**: a 200 Joule impact and 15 000 Newton compression resistant toe-cap, closed heel, antistatic shoe, fuel and oil resistant contact outsole, Energy absorbing heel, puncture resistant midsole, resistant to a 1 1100 Newtons, water penetration and absorption resistant upper, spiked outsole, puncture resistant outsole

SRC: Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. I Minor risks (auto-certification)

Retailer stamp

UPDATE 11/20/2020