

MULTIPURPOSE

LOW SHOE

LOW SHOES

S3

SRC

### The +

- Midsole with front protective covering
- Defined heel for better safety especially on ladders
- Insole breathable and anti-odor
- Reflective stripe with multiple faces



#### DESCRIPTION

AZURITE II shoes are made of waterproof grain leather. Its outsole is non-slip and resistant to oils and hydrocarbons and resists slipping on ceramic and steel floors. Its insole has an anti-odor treatment. PU reinforcement at the front of the foot. Non-woven lining and padded gusset.

#### SECTORS

Service

Second work

Handyman

Light industry

#### PURCHASE PACKAGING

REF.	EU	US	
9AZUL10036	36	4	6
9AZUL10037	37	4.5	6
9AZUL10038	38	5.5	6
9AZUL10039	39	6	6
9AZUL10040	40	7	6
9AZUL10041	41	8	6
9AZUL10042	42	8.5	6
9AZUL10043	43	9.5	6
9AZUL10044	44	10	6
9AZUL10045	45	11	6
9AZUL10046	46	11.5	6
9AZUL10047	47	12.5	6
9AZUL10048	48	13.5	6

## TECHNICAL FEATURES

<b>Closure</b>	Lacing	<b>Anti perforation sole</b>	Stainless less
<b>Toe cap</b>	Steel	<b>Work environment</b>	Multipurpose
<b>Sub-family</b>	Low shoe	<b>Color</b>	Black
<b>Upper</b>	Top grain leather	<b>Insole</b>	Removable and anti-odor
<b>Midsole</b>	Injected polyurethane	<b>Wearing sole</b>	Polyurethane
<b>Main assembly</b>	Injected assembly	<b>Lining</b>	Moisture wicking non-woven

## INSTRUCTIONS FOR USE AND STORAGE

### Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

### Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

### Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes.

## LEGISLATION

CE

EN ISO 20345:2011

**S3** **SRC**

**S3** : a 200 Joule impact and 15 000 Newton compression resistant toe-cap, closed heel, antistatic shoe, fuel and oil resistant contact outsole, Energy absorbing heel, puncture resistant midsole, resistant to a 1 1100 Newtons, water penetration and absorption resistant upper, spiked outsole, puncture resistant outsole  
**SRC** : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. I

Minor risks (auto-certification)

Retailer stamp