

Ref. **9CWFS80**

Synthetic Boots

PVC

Waders



S5

MADE IN
EUROPE

SR



LG



FO



The +

- 100% waterproof (works in water)
- SR: non-slip sole
- Oil-resistant and antistatic sole

PURCHASE PACKAGING

Ref.	Size	Carton
9CWFS80039	39	3
9CWFS80040	40	3
9CWFS80041	41	3
9CWFS80042	42	3
9CWFS80043	43	3
9CWFS80044	44	3
9CWFS80045	45	3
9CWFS80046	46	3
9CWFS80047	47	3

Some sizes may only be available in certain countries

DESCRIPTION

The WORT-IT CHEST SAFETY is a waterproof polyester-lined PVC wader. The high-grip outsole provides good slip resistance on ceramic surfaces. It protects against impact and penetration thanks to a protective steel toe cap and an anti-perforation steel midsole, and is equipped with an antistatic PVC sole that is resistant to hydrocarbons.

SECTORS

Farming, silviculture and fishing

Food-processing industry

Regional/public authorities

TECHNICAL FEATURES

Color	Green
Color 2	Black
Weight	2100 g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Steel
Outsole	PVC nitrile
Lining	Polyester

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These Chest Waders can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the Chest Waders, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the Chest Waders by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)



EPI CAT. II

EN ISO 20345:2022

S5

Safety shoes

S5 Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton and:- closed heel area- antistatic properties- energy-absorbing capacity of the heel Puncture resistance:- Sole puncture resistance (1100 Newton)- Metallic insert, 4.5mm diameter puncture needle- cleated outsole

SR

Resistance to slippage (ceramic floor + oil)

LG

Grip System - Unhooked heel

FO

Hydrocarbons resistance