

INDOOR & DRY ENVIRONMENTS

SANDAL



SANDALS

S1P SRC

The +

- Open shoe to be protected without suffering from heat
- Breathable upper and lining
- PU2D injected outsole: comfort and adherence

0% METAL

PURCHASE PACKAGING

REF.	EU	US	
9LAR120038	38	5.5	6
9LAR120039	39	6	6
9LAR120040	40	7	6
9LAR120041	41	8	6
9LAR120042	42	8.5	6
9LAR120043	43	9.5	6
9LAR120044	44	10	6
9LAR120045	45	11	6
9LAR120046	46	11.5	6
9LAR120047	47	12.5	6

DESCRIPTION

LARIMAR is a sandal with mesh and polyester upper which offer high breathability and comfort.
 Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption.
 Its removable insole, made of textile and EVA with wide perforations, offers good evacuation of perspiration.
 It is ideal for work dry environments.

SECTORS

Service

Second work

Handyman

Light industry

TECHNICAL FEATURES

Closure	Scratch	Anti perforation sole	Textile
Toe cap	Composite	Work environment	Indoor & dry environments
Sub-family	Sandal	Color	Black/blue/grey
Upper	Suede leather and polyester	Insole	Removable, perforated EVA
Midsole	Injected polyurethane	Wearing sole	Polyurethane
Main assembly	Injected assembly	Lining	Breathable 3D mesh

INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes.

LEGISLATION

CE

EN ISO 20345:2011

S1P **SRC**

S1P : Closed heel, antistatic shoe, fuel and oil resistant contact outsole, energy absorbing heel, puncture resistant midsole, resistant to a 1 100 Newtons pressure

SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. I

Minor risks (auto-certification)

Retailer stamp