

FIREMAN SABF RAC2 Boots



Reference: FIREMAN SABF RAC2 Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Comply with standards :

EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide (P)
- Isopropanol (Q)

EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

* Sizes 3 and 4.5 have steel toe cap and steel midsole.

Colors

Black



ATS sole
(registered
design)

Anti-perforation
+ Safety toe
cap

Polymer toe cap*

Composite anti-perforation
mid-sole*

Outside height (size 8): 330
mm

Weight (size 8): 2100g / pair

Elastomer: fireproofed NBR /
CR

(fireproofed
nitrile/polychloroprene rubber)

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14

Please contact us for sizes 3 and 4.5 certificate.



www.etchesecurite.com | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE |

+33 (0)5 59 28 05 41