SINGLE USE MASK FFP1D SL

Ref. 23101

TECHNICAL SHEET





MEASUREMENTS

Mask (mm)	139 x 127 x 54 (L x W x H)
Nose cushion (mm)	100 x 27 x 1.5 (L x W x T)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Sup. elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inf. elastic (mm)	265 x 5 x 0.55 (L x T x W)
Weight	12 g

GENERAL DESCRIPTION AND MATERIALS

- Single use protection mask FFP1D SL
- Filter Media : High Filtration Efficiency Melt-Blown (polypropylene)
- Synthetic rubber elastic without latex

- Outer layer in polypropylene
- Inner layer in polyester
- Aluminium pince-nez
- Nose cushion in polyethylene foam

SPECIFICAL ADVANTAGES

- · Allergic test
- Without latex

• Hygienic

MAIN APPLICATION FIELDS

- Protection against non toxic solid and liquid aerosols for concentration up to 4x0EL
- Do not use in a place where oxygene concentration is less than 17 % vol.
- Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, vegetable oils and soft woods
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods except)

PACKAGING

• 20 masks in a bag

• 240 masks in a box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 59765

Delivered by **BSI** (notified body n° 0086)

This mask is in conformity with the « French JO notice » 135 from 12th June 2004 and 226 from 28th September 2005.

EN 149 : 2001

SACLA - Z.I. de Rosarge - 01700 LES ECHETS - MIRIBEL - FRANCE

Tèl.: (33) 04 72 26 57 57 - Fax.: (33) 04 72 26 51 70 - Mail: contact@sacla-tm.fr