FOLDING SINGLE USE MASK FFP2D SL

Ref. 23200

TECHNICAL SHEET





MEASUREMENTS

Mask (mm)	Inferior part width : 85 Superior part width : 200 Height : 87
Pince-nez (mm)	90 x 9 x 0.5 (L x W x T)
Elastic (mm)	560 x 0.7 x 6 (L x T x W)

GENERAL DESCRIPTION AND MATERIALS

- Single use protection mask FFP2D SL
- Outer, inner and support layers in **polypropylene**
- Filter Media: High Filtration Efficiency Metl-Blown (polypropylene)

- Pince-nez in polyethylene encapsulated iron wire
- Natural rubber elastic

SPECIFICAL ADVANTAGES

- Allergic test
- Folding

- Resistant
- · Fire proof

MAIN APPLICATION FIELDS

- Protection against low toxicity solid and liquid aerosols in concentrations up to 12xOEL
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, lanoratories, medical controls
- Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (T.B.), chromium, manganese, nickel, platinum, strychnine, metal dust and smoke, viruses and enzymes
- Do not use in a place where oxygen concentration is less than 17 Vol. %

PACKAGING

- Individual packing
- 240 masks in a box

- 20 masks in a bag
- Distributor box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 59765

Delivered by BSI (notified body n° 0086)

This mask is in conformity with the « **French JO notice** » 135 from 06/12/04

EN 149: 2001

((

SACLA - Z.I. de Rosarge - 01700 LES ECHETS - MIRIBEL - FRANCE

Tèl.: (33) 04 72 26 57 57 - Fax.: (33) 04 72 26 51 70 - Mail: contact@sacla-tm.fr