# SINGLE USE MASK FFP2D SL

Ref. 23201

**TECHNICAL SHEET** 



# MEASUREMENTS

-	
MasK (mm)	139 x 127 x 54 (L x W x H)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Nose cushion (mm)	100 x 27 x 1.5 (L x W x T)
Superior elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inferior elastic (mm)	265 x 5 x 0.55 (L x W x T)

# **GENERAL DESCRIPTION AND MATERIALS**

• Singe use protection mask FFP2D SL

• Filter media : High Filtration Efficiency Melt-Blown (polypropylene), **electrostatic** 

- Synthetic rubber elastic, without latex
- Nose cushion in polyethylene foam

Aluminium pince-nez

### Resistance

- SPECIFICAL ADVANTAGES
  - Fire proof

#### MAIN APPLICATION FIELDS

• Protection against dust and low toxicity solid and liquid particles up to 12xOEL

•Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls • Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, hardwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis (TB)

• Outer and inner layers in **polypropylene** 

• Do not use in a place where oxygen concentration is less than 17 Vol. %

# PACKAGING

• 20 masks in a bag

# 240 masks in a box

# STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

#### The CE Type-examination certificate 59765

Delivered by BSI (notified body n° 0086)

#### EN 149:2001

This mask is in conformity with the « French JO notice » 135 from 06/12/004

CE

SACLA – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tèl. : (33) 04 72 26 57 57 - Fax. : (33) 04 72 26 51 70 - Mail : contact@sacla-tm.fr