

Art. 90310P



CORDURA

SCARPONE
BOOTS

CASTOR



TOMAIA: pelle Perwanger scamosciata idro colore grigio Husky
FODERA: membrana antiacqua Tepor
PROTEZIONE ANTITAGLIO: 8 strati
 Tallone rinforzato in TPU
PUNTALE: in acciaio
RINFORZO PUNTALE ESTERNO: in microfibra trattata PU
LAMINA: tessuto multistrato
SUOLA: gomma nitrilica antiolio, anticalore, antistatica, antiscivolo con rampone contro lo scivolamento laterale sui tronchi
PLANTARE: anatomico
FONDO FLESSIBILE: consente di avere maggiore sensibilità, ideale anche per chi utilizza i macchinari
NUMERAZIONE: dal 36 al 50

UPPER: grey Husky water-resistant suede Perwanger leather
 LINING: Tepor waterproof membrane
 CUT PROTECTION: 8 layers
 Reinforced TPU heel
 TOE CAP: steel
 EXTERNAL TOE REINFORCEMENT: PU-treated microfiber
 MIDSOLE: multilayer fabric
 SOLE: oil-resistant, heat-resistant, antistatic, slip-resistant nitrile rubber with side-slip cleat for logs
 FOOTBED: anatomical
 FLEXIBLE SOLE UNIT: provides greater sensitivity, ideal for machinery operators
 SIZES: 36-50

Norme - Standards

EN ISO 17249:2013 LIV3

EN ISO 20345:2022 + A1:2024 protezione S7L-FO-HRO-HI-CI-SR

Art. 90312

SCARPONE
BOOTS

SORAPIS



TOMAIA: pelle nera
FODERA: in TNT traspirante
PROTEZIONE ANTITAGLIO: 8 strati
 Tallone rinforzato in TPU
PUNTALE: in acciaio
RINFORZO PUNTALE ESTERNO: in microfibra trattata PU
LAMINA: tessuto multistrato
SUOLA: gomma nitrilica antiolio, anticalore, antistatica, antiscivolo con rampone contro lo scivolamento laterale sui tronchi
PLANTARE: anatomico
FONDO FLESSIBILE: consente di avere maggiore sensibilità, ideale anche per chi utilizza i macchinari
NUMERAZIONE: dal 36 al 50

UPPER: black leather
 LINING: breathable TNT
 CUT PROTECTION: 8 layers
 Reinforced TPU heel
 TOE CAP: steel
 EXTERNAL TOE REINFORCEMENT: PU-treated microfiber
 MIDSOLE: multilayer fabric
 SOLE: oil-resistant, heat-resistant, antistatic, slip-resistant nitrile rubber with side-slip cleat for logs
 FOOTBED: anatomical
 FLEXIBLE SOLE UNIT: provides greater sensitivity, ideal for machinery operators
 SIZES: 36-50

Norme - Standards

EN ISO 17249:2013 LIV 2

EN ISO 20345:2022 + A1:2024 protezione S3-PL-FO-HRO-CI-SR